










<b>PHOTOELECTRIC SENSORS</b>	
<a href="#"><u>General Specification</u></a>	
<a href="#"><u>18 Series M18 Tubular</u></a>	
<a href="#"><u>MF Series M18 with sensitivity adi.</u></a>	
<a href="#"><u>FQ Series 50x50mm compact</u></a>	
<a href="#"><u>FW Series 81x67,5 mm rectang. PG13.5 conn.</u></a>	
<a href="#"><u>FF Series Optical bracket</u></a>	
<a href="#"><u>AF Series Amplifier for opt. Fibers</u></a>	
<a href="#"><u>MR Series Contrast sensors</u></a>	
<a href="#"><u>MT series Photoelectric sens. in miniature housing</u></a>	
<a href="#"><u>FQL Series 50x50x15mm compact size</u></a>	

**PHOTOELECTRIC SENSORS**  
 FW Series - 81x67, 5 mm  
 Rectangular PG13.5 Connector

[General Specification](#)

[Thru Beam](#)



Diffuse Reflective



Retro Reflective



Background Suppression



Foreground Suppression

[Please Click the wording \( Blue Color\) for the Link to the Specification Data sheet.](#)

DIFFUSE REFLECTIVE TYPE	RETRO REFLECTIVE TYPE	BACKGROUND SUPPRESSION TYPE	FOREGROUND SUPPRESSION TYPE
<a href="#"><u>12-30 V DC NPN/PNP OUTPUT</u></a>	<a href="#"><u>12-30 V DC NPN/PNP OUTPUT</u></a>	<a href="#"><u>12-30 V DC NPN/PNP OUTPUT</u></a>	<a href="#"><u>14-230 V AC/DC RELAY OUTPUT</u></a>
<a href="#"><u>14-230 V AC/DC RELAY OUTPUT</u></a>	<a href="#"><u>14-230 V AC/DC RELAY OUTPUT</u></a>	<a href="#"><u>14-230 V AC/DC RELAY OUTPUT</u></a>	<a href="#"><u>12-30 V DC PROGRAMMABLE OUTPUT</u></a>
		<a href="#"><u>12-30 V DC PROGRAMMABLE OUTPUT</u></a>	